

CABLE STANDARDS

IEC 60502-2 , ISIRI 3569-2 , IEC 60228, IEC 60332-1-2



APPLICATION

To be laid directly in ground, outdoors, indoors and in cable ducts. Medium voltage cables for distribution networks, also for connection to generation units and and also for places where plant and process connection .there are mechanical stresses

CONSTRUCTION

Conductor

Class 2 stranded aluminum conductor

Inner Semi-Conductive Layer

Semi-conductive material

Insulation

XLPE (Cross-Linked Polyethylene)

Outer Semi-Conductive Layer

Semi-conductive material

Screen

Copper wires with copper tape

Bedding

PVC (Polyvinyl Chloride)

Armour

Steel (Galvanized) Wire

Sheath

PVC (Polyvinyl Chloride)

CHARACTERISTICS

Voltage Rating (U₀,U) (Um)

3.6/6 (7.2) kV

Test Voltage

12.6 KV

Temperature Rating

-20°C to +90°C

Short Circuit Temperature

+250°C

Minimum Bending Radius

15 x Overall Diameter

Sheath Color

Red

NA2XSEYRY

AL/SC/ XLPE/ SC/ SCT/ CWS/ PVC/ SWA/ PVC – 3.6/6 (7.2) kV Cable

Technical Specifications

NO. OF CORES	NOMINAL CROSS SECTIONAL AREA		Max DC Conduc tor Resista nce at 20°C Ω.km	Short- circuit Current KA 1.sec Approx	CURRENT CARRYING CAPACITY Amps Approx				Capacitance μf.km Approx	Reactance Ω.km Approx		OVERALL DIAMETER Mm Approx	WEIGHT kg.km Approx
	Conductor mm ²	Screen mm ²			Trefoil		Flat			Trefoil	Flat		
			Ground	Air	Ground	Air							
3	25	16	1.20	2.5	119	124	-	-	0.19	0.19	0.27	47.0	4039
3	35	16	0.868	3.4	144	151	-	-	0.21	0.19	0.26	49.5	4438
3	50	16	0.641	4.9	171	181	-	-	0.23	0.18	0.25	51.7	4786
3	70	16	0.443	6.8	209	226	-	-	0.27	0.17	0.25	55.9	5443
3	95	16	0.320	9.2	249	275	-	-	0.31	0.17	0.24	60.4	6391
3	120	16	0.253	11.6	283	317	-	-	0.34	0.16	0.24	64.4	7248
3	150	25	0.206	14.5	316	359	-	-	0.37	0.16	0.23	67.5	7712
3	185	25	0.164	17.8	358	412	-	-	0.40	0.15	0.23	71.6	8585
3	240	25	0.125	23.1	416	489	-	-	0.37	0.15	0.23	79.4	11267
3	300	25	0.100	28.8	469	559	-	-	0.50	0.15	0.23	85.0	13067
3	400	35	0.0778	38.3	532	651	-	-	0.57	0.15	0.22	94.5	16232
3	500	35	0.0605	47.8	599	744	-	-	0.62	0.14	0.22	101.7	18877
3	630	35	0.0469	60.2	669	843	-	-	0.65	0.14	0.22	112.5	23102